

**360 SERIES
SPECIFICATION SHEETS
2000-2002**

2000	Specification Sheet	CC
2001	Specification Sheet	CC
2002	Specification Sheets	CC

Material contained in this document is intended for use by Independent Retail dealer personnel.

Any other use without expressed written consent of MTD PRODUCTS INC is prohibited.

364	18 H.P. Briggs	Twin	Dual Hydro	2000
365	20 H.P. Command	Twin	Dual Hydro	2000
365L	18 H.P. Kawasaki	Twin	Dual Hydro	2000

MODEL: 364**YEAR: 2000-2002**Factory Model Number: **53AA1A5L100****18 H.P. Hydro Drive
Electric P.T.O. / 44" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	700 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	20" x 8.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Industrial Plus (Vertical)
Model/Type/Spec	407777-0128-E1
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	18 HP
Peak Torque	Not Available
Displacement	40.0 cu in. (656cc)
Bore	2.97"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1400 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-499486S
Pre Filter	BS-273638S
Oil Filter	BS-492932S
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-797890

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	BS-845907
Solenoid	725-3001
Muffler	751-0616B
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3467

ENGINE:

Complete Engine	BS-44K777-0027
Short Block	BS-698172
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: 365**YEAR: 2000-2002**Factory Model Number: **53CA1B6K100****20 H.P. Hydro Drive
Electric P.T.O. / 54" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	740 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	22" x 11.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Command (Vertical)
Model/Type/Spec	CV20S-65558
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	33.3 ft. lbs. @ 2,200 R.P.M.
Displacement	38.0 cu in. (624cc)
Bore	3.03"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1400 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	Hydraulic
Valve Lash (Exhaust)	Hydraulic
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-47-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-18-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	KH-41-403-10-S
Solenoid	KH-52-435-02
Muffler	751-0805A
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3389

ENGINE:

Complete Engine	Not Available
Short Block	KH-24-522-222
Mini Block	KH-24-782-24

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: 365L**YEAR: 2000-2002**Factory Model Number: **53CA1D5K100****18 H.P. Hydro Drive
Electric P.T.O. / 54" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	750 lbs.
Engine Type	Gas (Liquid Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Smooth/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	22" x 11.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FD (Vertical)
Model/Type/Spec	FD590V-AS06
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	18 HP
Peak Torque	Not Available
Displacement	35.7 cu in. (585mL)
Bore	2.90"
Stroke	2.66"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3400 R.P.M.
Max. Speed (Full Load)	3350 R.P.M.
Valve Lash (Intake)	0.010"
Valve Lash (Exhaust)	0.010"
Ignition Type	Electronic
Spark Plug Gap	0.024"-0.028"
Mag Air Gap	0.012"-0.050"

CAPACITIES:

Engine Crankcase	70.9 oz. (A)
Coolant	3.2 qts. (E)
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034
(E) 50/50 Mixture	

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-2205
Pre Filter	KM-11013-2114
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-1055
Spark Plug	KM-BMR6A
Armature	KM-21121-2083
Igniter	KM-21119-2120
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	KM-21066-2070
Solenoid	KM-27010-7005
Muffler	KM-4907024359Y (N.L.A.)
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3389

ENGINE:

Complete Engine	Not Available
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

364	18 H.P. Briggs	Twin	Dual Hydro	2001
365	20 H.P. Command	Twin	Dual Hydro	2001
365L	18 H.P. Kawasaki	Twin	Dual Hydro	2001

MODEL: 364**YEAR: 2000-2002**Factory Model Number: **53AA1A5L100****18 H.P. Hydro Drive
Electric P.T.O. / 44" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	700 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	20" x 8.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Industrial Plus (Vertical)
Model/Type/Spec	407777-0128-E1
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	18 HP
Peak Torque	Not Available
Displacement	40.0 cu in. (656cc)
Bore	2.97"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1400 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-499486S
Pre Filter	BS-273638S
Oil Filter	BS-492932S
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-797890

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	BS-845907
Solenoid	725-3001
Muffler	751-0616B
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3467

ENGINE:

Complete Engine	BS-44K777-0027
Short Block	BS-698172
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: 365**YEAR: 2000-2002**Factory Model Number: **53CA1B6K100****20 H.P. Hydro Drive
Electric P.T.O. / 54" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	740 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	22" x 11.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Command (Vertical)
Model/Type/Spec	CV20S-65558
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	33.3 ft. lbs. @ 2,200 R.P.M.
Displacement	38.0 cu in. (624cc)
Bore	3.03"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1400 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	Hydraulic
Valve Lash (Exhaust)	Hydraulic
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-47-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-18-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	KH-41-403-10-S
Solenoid	KH-52-435-02
Muffler	751-0805A
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3389

ENGINE:

Complete Engine	Not Available
Short Block	KH-24-522-222
Mini Block	KH-24-782-24

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: 365L**YEAR: 2000-2002**Factory Model Number: **53CA1D5K100****18 H.P. Hydro Drive
Electric P.T.O. / 54" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	750 lbs.
Engine Type	Gas (Liquid Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Smooth/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	22" x 11.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FD (Vertical)
Model/Type/Spec	FD590V-AS06
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	18 HP
Peak Torque	Not Available
Displacement	35.7 cu in. (585mL)
Bore	2.90"
Stroke	2.66"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3400 R.P.M.
Max. Speed (Full Load)	3350 R.P.M.
Valve Lash (Intake)	0.010"
Valve Lash (Exhaust)	0.010"
Ignition Type	Electronic
Spark Plug Gap	0.024"-0.028"
Mag Air Gap	0.012"-0.050"

CAPACITIES:

Engine Crankcase	70.9 oz. (A)
Coolant	3.2 qts. (E)
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034
(E) 50/50 Mixture	

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-2205
Pre Filter	KM-11013-2114
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-1055
Spark Plug	KM-BMR6A
Armature	KM-21121-2083
Igniter	KM-21119-2120
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	KM-21066-2070
Solenoid	KM-27010-7005
Muffler	KM-4907024359Y (N.L.A.)
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3389

ENGINE:

Complete Engine	Not Available
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

364	18 H.P. Briggs	Twin	Dual Hydro	2002
365	20 H.P. Command	Twin	Dual Hydro	2002
365L	18 H.P. Kawasaki	Twin	Dual Hydro	2002

MODEL: 364**YEAR: 2000-2002**Factory Model Number: **53AA1A5L100****18 H.P. Hydro Drive
Electric P.T.O. / 44" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	700 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	20" x 8.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Industrial Plus (Vertical)
Model/Type/Spec	407777-0128-E1
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	18 HP
Peak Torque	Not Available
Displacement	40.0 cu in. (656cc)
Bore	2.97"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1400 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-499486S
Pre Filter	BS-273638S
Oil Filter	BS-492932S
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-797890

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	BS-845907
Solenoid	725-3001
Muffler	751-0616B
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3467

ENGINE:

Complete Engine	BS-44K777-0027
Short Block	BS-698172
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: 365**YEAR: 2000-2002**Factory Model Number: **53CA1B6K100****20 H.P. Hydro Drive
Electric P.T.O. / 54" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	740 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	22" x 11.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Command (Vertical)
Model/Type/Spec	CV20S-65558
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	33.3 ft. lbs. @ 2,200 R.P.M.
Displacement	38.0 cu in. (624cc)
Bore	3.03"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1400 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	Hydraulic
Valve Lash (Exhaust)	Hydraulic
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-47-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-18-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	KH-41-403-10-S
Solenoid	KH-52-435-02
Muffler	751-0805A
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3389

ENGINE:

Complete Engine	Not Available
Short Block	KH-24-522-222
Mini Block	KH-24-782-24

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: 365L**YEAR: 2000-2002**Factory Model Number: **53CA1D5K100****18 H.P. Hydro Drive
Electric P.T.O. / 54" Deck****GENERAL INFO:**

Length (Over-All)	Not Available
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	750 lbs.
Engine Type	Gas (Liquid Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	Not Available
Tread Front/Rear	Smooth/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4.0"-5"
Rear Wheel Tire Size	22" x 11.0"-8
Trans/Differential Type	Aluminum, Bi-Directional
Forward Speed	0-7.0 mph
Reverse Speed	0-4.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FD (Vertical)
Model/Type/Spec	FD590V-AS06
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	18 HP
Peak Torque	Not Available
Displacement	35.7 cu in. (585mL)
Bore	2.90"
Stroke	2.66"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3400 R.P.M.
Max. Speed (Full Load)	3350 R.P.M.
Valve Lash (Intake)	0.010"
Valve Lash (Exhaust)	0.010"
Ignition Type	Electronic
Spark Plug Gap	0.024"-0.028"
Mag Air Gap	0.012"-0.050"

CAPACITIES:

Engine Crankcase	70.9 oz. (A)
Coolant	3.2 qts. (E)
Transmission	11 qts. (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	4.5 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034
(E) 50/50 Mixture	

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-2205
Pre Filter	KM-11013-2114
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-1055
Spark Plug	KM-BMR6A
Armature	KM-21121-2083
Igniter	KM-21119-2120
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	723-3071
Voltage Regulator	KM-21066-2070
Solenoid	KM-27010-7005
Muffler	KM-4907024359Y (N.L.A.)
Battery	725-1722 (N.L.A.)
Relays	725-1718
P.T.O. Clutch	917-3389

ENGINE:

Complete Engine	Not Available
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
Limited Commercial	1 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.